



MATERIAL SAFETY DATA SHEET SUPERIOR No. 96T

DATE REVISED: February 9, 2004



Product Name: Superior No. 96T

Manufacturer: Superior Flux & Mfg. Co. 6615 Parkland Blvd. Cleveland, OH 44139

Emergency Phone Number: 1-800-424-9300 (CHEMTREC)

Other Information Calls: (440) 349-3000

To the Purchaser: This MSDS contains important environmental, health, and toxicology information for your employees who have ordered this product. Please be sure this information is given to them. If you resell this product, a copy of the MSDS should be given to the buyer.

H.M.I.S. INFORMATION: HEALTH = 1 FLAMMABILITY = 3 REACTIVITY = 0

SECTION I - IDENTIFICATION

Common Name: Superior No. 96T

Chemical Family: Alcohol Thinner

CAS Number: NA

Chemical Name: NA

Formula: See Below

SECTION II - COMPOSITION INFORMATION

<u>Components</u>	<u>CAS Number</u>	<u>%</u>	<u>OSHA PEL</u>
Isopropanol	67-63-1	75-85	400PPM
Mineral Spirits	8032-32-4	15-25	500PPM

Unlisted percentages are non-hazardous stabilizers, activators, and water. None of the materials in this product are listed in NTP, IARC, or OSHA as carcinogens.

SECTION III - HEALTH HAZARDS

Primary Routes of Entry: Fume Inhalation, Ingestion, Skin, and Eyes.

Symptoms of Overexposure: Dizziness, Blurred Vision, Headache, Irritation of Mucous Membranes, Loss of Appetite.

Medical Conditions Generally Aggravated by Overexposure: Skin Conditions, Kidney or Liver Diseases.

Chemical Listed as a Carcinogen or Potential Carcinogen: None

OSHA Permissible Exposure Limit (PEL): 400 PPM

ACGIH Threshold Limit Value (TLV): 400 PPM

SECTION IV - EMERGENCY AND FIRST AID PROCEDURES

Eyes: Flush with Water for 10 Minutes. Call a Physician.

Skin: Wash Thoroughly with Water.

Inhalation: Remove to Fresh Air or Administer Oxygen. Call Physician.

Ingestion: Do Not Induce Vomiting. Drink Lots of Water. Obtain Medical Attention Immediately.

Superior manufactures quality fluxes. Our business is solving problems.



SECTION V - FIRE AND EXPLOSION HAZARD DATA

Flash Point: 18.3°C/65°F

Flammable Limits: Lower-2 Upper-12

Extinguishing Media: Dry Chemical, CO₂

Auto Ignition Temperature: 398°C/750°F

Special Fire Fighting Procedures: Wear Protective Clothing, Including NIOSH Approved Self-Contained Breathing Apparatus

Unusual Fire and Explosion Hazards: Flammable, Do Not Mix with Strong Oxidizing or Dehydrating Agents. Do Not Store in Presence of Oxidizing Agents

SECTION VI - ACCIDENTAL RELEASE MEASURES

Steps to be Taken in Case Material is Spilled: Absorb with Sawdust and Remove in Accordance to EPA Regulations.

SECTION VII - HANDLING AND STORAGE

Storage Requirements: Store in Plastic Containers in Cool Area. Do Not Store in Glass Containers.

Handling Precautions: Safe Precautionary Practices.

Other Precautions: Keep Away From Electrical Sparks, Heat, Open Flame or Oxidizing Agents.

SECTION VIII - CONTROL MEASURES

Respiratory Protection (TYPE): NIOSH Approved Respirator.

Ventilation: Yes

Mechanical (General): Explosion Proof

Local Exhaust: Yes

Eye Protection: Safety Glasses

Protective Gloves: Recommended, NIOSH Approved

Other Protective Clothing or Equipment: Rubber Apron is Recommended

SECTION IX - PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling Point: 82°C/179.6°F

Specific Gravity (Water = 1): 0.784

Vapor Pressure (mm Hg): 33

Percent Volatile by Volume: 99%

Vapor Density (Air = 1): 2.07

Evaporation Rate (Butyl Acetate = 1): 2.88

Melting Point: -88°C/-127°F

Solubility in Water: Unlimited

Reactivity in Water: None

Appearance and Odor: Clear Liquid, Alcohol Odor

SECTION X - STABILITY AND REACTIVITY

Stability: Product is Stable

(Conditions to Avoid): NA

Incompatibility: Strong Oxidizers.

Hazardous Decomposition Products: CO.

Hazardous Polymerization: NA

(Conditions to Avoid): NA

MSDS: Superior No. 96T P. 2/3

The information contained herein is based on data considered to be accurate and is intended for use by persons having technical skills at their own discretion and risk. Since conditions of use are outside of Superior Flux & Mfg. Co.'s control, we cannot assume liability for results obtained or damage incurred due to misuse, nor can we assume customer liability.

Superior manufactures quality fluxes. Our business is solving problems.



**Superior Flux
& Mfg. Co.**

6615 Parkland Blvd. • Cleveland, OH 44139 • Phone: 440-349-3000 • Fax: 440-349-3003
www.superiorflux.com • e-mail: info@superiorflux.com

SECTION XI - TOXICOLOGICAL INFORMATION

Isopropanol

Acute Toxicity Data:

- 1) **Oral:** LD-50 (rat): 5840mg/kg
- 2) **Inhalation:** LC-50 (rat): 12000 PPM/8 hours
- 3) **Dermal:** LD-50 (rabbit): 13000mg/kg
- 4) **Skin Irritation:** (rabbit): Slight

Chronic Toxicity Data:

- 1) **Repeated Skin Application:** (rat) Slight Irritation
- 2) **Eye Irritation:** (rabbit) Slight to Severe

SECTION XII - ECOLOGICAL INFORMATION

This Material has not been Tested for Environmental Effects.

SECTION XIII - DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in Accordance with EPA Regulations

SECTION XIV- TRANSPORTATION

D.O.T. Proper Shipping Name: Isopropanol

Hazard Class: 3

Identification Number: UN1219

Packing Group: II

Type D.O.T Label Required Information: Flammable Liquid

SECTION XV - REGULATORY INFORMATION

OSHA Hazardous Chemical According to 29 CFR 1910.1200: Isopropyl Alcohol

Carcinogenicity Classification: (Components Present at 0.1% or More)

International Agency for Research on Cancer (IARC): Not Listed

American Conference of Governmental Industrial Hygienists (ACGIH): Not Listed

National Toxicology Program (NTP): Not Listed

Occupational Safety and Health Administration (OSHA): Not Listed

All Components of this Product are Listed on the U.S. Toxic Substances Control Act Inventory or Otherwise Comply with TSCA Pre-manufacture Notification Requirements.

SECTION XVI - OTHER INFORMATION

Disclaimer: Judgments as to the suitability of information herein or the purchaser's purposes are necessarily the purchaser's responsibility. Reasonable care has been taken in the preparation of this material, but there are NO WARRANTIES, NO REPRESENTATIONS, AND NO RESPONSIBILITY AS TO THE ACCURACY OR THE SUITABILITY OF THIS INFORMATION FOR ANY PURCHASER'S USE OR FOR ANY CONSEQUENCE TO USE.

MSDS: Superior No. 96T P. 3/3

The information contained herein is based on data considered to be accurate and is intended for use by persons having technical skills at their own discretion and risk. Since conditions of use are outside of Superior Flux & Mfg. Co.'s control, we cannot assume liability for results obtained or damage incurred due to misuse, nor can we assume customer liability.

Superior manufactures quality fluxes. Our business is solving problems.



**Superior Flux
& Mfg. Co.**

6615 Parkland Blvd. • Cleveland, OH 44139 • Phone: 440-349-3000 • Fax: 440-349-3003
www.superiorflux.com • e-mail: info@superiorflux.com